

SERVICE TO BE PERFORMED	COMPLETE	NEEDS REPAIR (EXPLANATION)
MAKE SURE TANK IS EMPTY		
CHECK HYDRAULIC FLUID LEVEL - CHANGE ANNUALLY (For <= 10 gallon system)		
CHECK BLOWER OIL LEVEL - CHANGE ANNUALLY		
CHECK BODY/BOOM SEALS CONDITION and for LEAKAGE		
INSPECT ALL WATER HOSES/LINES FOR LEAKS or WEAR		
CHECK TRANSFER CASE OIL LEVEL ANNUALLY		
GREASE ROTATING BEARING ON HOSE REEL (bearing must be rotated 2 full turns)		
GREASE HOSE REEL SHAFT BEARINGS		
GREASE DEBRIS BODY FILL INDICATOR (2) - CHECK FOR PROPER OPERATION		
INSPECT and ROTATE SUCTION HOSE		
INSPECT BOOM SLEEVE SWINGING COMP for WEAR or EXCESSIVE PLAY		
INSPECT and LUBRICATE THE FOLLOWING:		
BOOM SLEEVE, LIFT CYLINDER and HINGE PINS		
DEBRIS BODY HOIST CYLINDERS, BODY HINGES and BODY DOOR HINGES		
BLOWER BEARINGS		
INSPECT BIN HEATER		
CHECK OPERATION OF PRESSURE LIMITING DEVICE (Kunkle Valve, Hydraulic Relief Valve and Water Relief Valve) IF SO EQUIPPED		
CHECK ALL COMPONENT MOUNTING BOLTS, PINS, ETC.		
LUBRICATE ALL COMPARTMENT LATCHES and HINGES		
CHECK OPERATIONAL DECALS and SAFETY STICKERS		